Non-glass, unbreakable pH electrode Advanced micro-electronics eliminates the problems of delicate glass pHmeters, and enable to measure samples as small as a single drop.



686

Convenient one-point calibration





Reference Electrode (replacement parts)

Overseas Sales Agency:

ICHIRO

Ichiro Corporation
http://www.ichiro-corporation.jp/



Features

Non-glass, unbreakable silicon mico-sensors Convenient one-point calibration

(One point cablibration is enough, but two points calibration is also possible.)

Waterproof

- •Stable readings in seconds, fast rsponse time
- Automatic temperature compensation(ATC)
- •Automatic buffer recognition

Measure samples as small as one drop Replaceable reference electrode

- •Display pH and temperature
 - Over 150 hours on one watch battery
 - •Automatic power off
 - Error messages alert you to incorrect calibration or meter failures

Product Sensor roduct

Range Resolution Accuracy Stability indicator Measuring Temperature Operating Temp.
Waterproof
Function

Battery life Dimensions Weight Accessories

Reference

S2K712

SEK/IZ
Silicon chip ISFET
On chip Temp. sensor
2~12pH 0~50°C
0.01pH ± 1°C
±0.05pH ±1°C
>±0.02pH
5~40°C
Debugs ON: "5114" Power ON: "pH/temp." in turn IP67 One-point (2-points) calibration Automatic temperature compensation Waterproof Automatic power off Error messages

arour messages
3V lithium battery CR2032 x1
150 hours (approx.)
142×28x15mm
42g (0.1 lbs.) Users manual, pH7.01 standard buffer, carry case Cosumable Part No.R2K712

S2K922

Sched Silicon chip ISFET On chip Temp. sensor 2~12pH 0~50°C 0.01pH ± 1°C ±0.02pH ±1°C >±0.02pH 5~40°C 5~40℃ Power ON: "pH/temp." in turn **IP67** One-point (2-points) calibration Automatic temperature compensation Waterproof Automatic power off Error messages Error messages
3V lithium battery CR2032 x1
150 hours (approx.)
142×28x15mm
42g (0.1 lbs.)
Users manual, PH7.01 standard buffer, carry case Cosumable Part No.R2K712

•Data subject to change without notice. •Descriptions of this brochure are things as of May, 2011.



Overseas Sales Agency

ICHIRO

Ichiro Corporation

2-3-20 Sarue, Kotoku, Tokyo 135-0003 TEL/FAX 81-3-6823-8514 E-mail: info@ichiro-corporation.jp